

N

ELECTRICAL ENERGY AUDIT IN PRATAMA TAPAN HOSPITAL

TUGAS AKHIR

Diajukan sebagai salah satu syarat untuk memperoleh Gelar Sarjana Teknik pada Q Program Studi Teknik Elektro Fakultas Sains dan Teknologi З





Oleh:

NANDA OKTA PUTRA

11950515439

State Islamic Univer **PROGRAM STUDI TEKNIK ELEKTRO** FAKULTAS SAINS DAN TEKNOLOGI UNIVERSITAS ISLAM NEGERI SULTAN SYARIF KASIM RIAU L V PEKANBARU of Sultan Syarif Kasim Ria

2023

Hak Cipta Dilindungi Undang-Undang

I

a

× C

- Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber:
- a Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.

Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau



N

Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau

0

Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber:

Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah

0

Т

ak c

ipta

milik

IN Sus

ka

Riau

State Islamic University of Sultan Syarif Kasim R

LEMBAR PENGESAHAN

AUDIT ENERGI LISTRIK RUMAH SAKIT PRATAMA TAPAN

TUGAS AKHIR

oleh :

<u>NANDA OKTA PUTRA</u> 11950515439

Telah dipertahankan di depan Sidang Dewan Penguji sebagai salah satu syarat untuk memperoleh gelar Sarjana Teknik Fakultas Sains dan Teknologi Universitas Islam Negeri Sultan Syarif Kasim Riau di Pekanbaru, pada tanggal 17 November 2023

Pekanbaru, 17 November 2023

Mengesahkan,

Dekan Fakultas Sains dan Teknologi Dr. Hartono, M.Pd STAINTP. 19640301 199203 1 003

Ketua Prodi Teknik Elektro

Dr. Zulfatri Aini, S.T.,M.T NIP. 19721021 200604 2 001

DEWAN PENGUJI:

Ketua	: Ahmad Faizal, S.T.,M.T
Sekretaris	: Dr. Zulfatri Aini, S.T.,M.T
Anggota 1	: Dr. Liliana, S.T.,M.Eng
Anggota 2	: Nanda Putri Miefthawati, B.Sc.,M.Sc



N

0

Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau.

Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau

a. Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.

State Islamic University of Sultan Syarif Kasim R

0

Hak

cipta

milik

z S

S ka

R

8

LEMBAR PERSETUJUAN

AUDIT ENERGI LISTRIK RUMAH SAKIT PRATAMA TAPAN

TUGAS AKHIR

oleh:

NANDA OKTA PUTRA 11950515439

Telah diperiksa dan disetujui sebagai laporan Tugas Akhir Program Studi Teknik Elektro di Pekanbaru, pada tanggal 17 November 2023

Ketua Prodi Teknik Elektro

Dr. Zulfatri Aini, S.T.,M.T NIP. 19721021 200604 2 001 Pembimbing

Dr. Zulfatri Aini, S.T., M.T NIP. 19721021 200604 2 001



N

0 Т ۵ ~ B C

State Islamic University of Sultan Syarif Kasim R

Hak Cipta Dilindungi Undang-Undang

C Ipta milik z S S ka R

Nomor : 25/2021 Tanggal : 10 September 2021

SURAT PERNYATAAN

Saya yang bertanda tangan di bawah ini:

Nama	: Nanda Okta Putra
NIM	: 11950515439
Tempat/Tgl. Lahir	: Tapan, 16 Oktober 2000
Fakultas	: Sains dan Teknologi
Prodi	: Teknik Elektro
Judul Jurnal	:

ELECTRICAL ENERGY AUDIT IN PRATAMA TAPAN HOSPITAL

Menyatakan dengan sebenar-benarnya bahwa :

- 1. Penulisan Jurnal dengan judul sebagaimana tersebut di atas adalah hasil pemikiran dan penelitian saya sendiri.
- 2. Semua Kutipan pada Karya tulis saya ini sudah disebutkan sumbernya.
- 3. Oleh karena itu Jurnal saya ini, saya nyatakan bebas dari plagiat.
- 4. Apa bila dikemudian hari terbukti terdapat plagiat dalam penulisan Jurnal saya tersebut, maka saya bersedia menerima sanksi sesuai peraturan perundang-undangan.

Demikianlah surat pernyataan ini saya buat dengan penuh kesadaran dan tanpa paksaan dari pihak manapun juga.

Pekanbaru, 28 November 2023 Yang membuat pernyataan JX671740180 Nanda Okta Putra NIM. 11950515439

0 Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber:



R

Hak Cipta Dilindungi Undang-Undang

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber



Volume xx, No. xx, Month 20xx, pages xx - xx





Electrical Energy Audit in Pratama Tapan Hospital

Nanda Okta Putra¹ (²²³⁾, Zulfatri Aini¹, Dila Marta Putri² ¹ Universitas Islam Negeri Sultan Syarif Kasim Riau, Riau, Indonesia ²Institut Teknologi Bisnis Riau, Riau, Indonesia nandaoktaputraa@gmail.com

Abstract- Hospitals, as large energy consumers, must adopt efficient energy-saving measures due to cost increases, regulations, and climate change concerns. In this study, an electrical energy audit was conducted at Pratama Tapan Hospital to identify energy-saving opportunities and recommend equipment replacements or technology upgrades. The primary objective was to determine the Energy Consumption Intensity (ECI) and analyze the potential for energy savings. The audit revealed an ECI value of 10.33 kWh/m²/year, highly efficient by ASEAN-USAID standards. However, 100% of rooms didn't meet the SNI 03-6197-2000 light intensity standard, causing discomfort. The study recommends installing specific light fixtures and adjusting lamp power to comply with the standard. These findings offer valuable insights for healthcare institutions striving to achieve sustainability goals.

Keywords: Energy audit, energy efficiency, hospital, ECI, lighting

1 Introduction

Electrical energy has an important role in human life. Along with technology development, relectricity is needed in various sectors such as education, government, agriculture, and health. Research [1] states that Indonesia is one of the countries with considerable use of electrical energy. This can cause an electrical energy crisis that will impact the environment, society, and economy. Therefore, an effort is needed to reduce electricity usage in all these sectors to overcome excess electrical energy. la

Based on Indonesian policy ESDM No. 13 of 2012 regarding the saving of electricity Econsumption, all government office buildings, both services and services, must carry out energy ^o management so that the electricity Energy Consumption Intensity (ECI) becomes organized and can Cachieve efficient use. One of the main strategies of energy management that can be done is energy Econservation. Some methods are commonly applied in energy conservation, namely retrofitting, technology upgrades, and energy-saving behavior. An energy audit process in the energy conservation process is a calculation method to obtain energy consumption in one or more buildings [2]. Energy audits also aim to identify energy consumption and seek efforts to improve energy efficiency.

Several researchers have previously conducted many studies on energy audits, such as in windustrial buildings [3, 4], Higher Education [5-7], Office [8], Apartment [9, 10], and Hospitals [11-13]. Based on these studies, it can be concluded that electrical energy audits must be carried out in buildings that have a high intensity of electrical energy usage. Therefore, based on Government Regulation No. 70 of 2009 Article 12, hospitals have large energy consumption and are included in the mondatory energy energy energy consumption and are included in Since 12, nospitals have large energy consumption and are include intensity of continuous energy use, such as inpatient rooms, lighting, medical devices, cooling the mandatory energy management or conservation category. Research [14, 15] stated that the high



Hak Cipta Dilindungi Undang-Undang Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber I C

0

²⁰systems, and air purifiers, causes high energy consumption in hospital buildings. The larger or taller the hospital building construction, the more energy is used to operate the facility.

Therefore, in this research, an electrical energy audit was conducted at Pratama Tapan Hospital, • which is a type D hospital. The need for more lighting comfort in this hospital was found based on interviews and surveys. This is caused by several factors, such as if the weather is cloudy, intense ighting in the Hospital Building is very dim, especially in certain rooms that do not get direct light from the sun so that it can interfere with the comfort of work. From the survey, it was also found that the lack of use of air conditioners in this hospital. This can be seen from all inpatient rooms; Tonly seven rooms are installed with Air Conditioners.

From these problems, the authors conducted energy audit case research at Pratama Tapan Hospital, Basa Ampek Balai Tapan sub-district, Pesisir Selatan district, and West Sumatra province. The Pesisir Selatan regional government manages this hospital with a land area of 40,000 m². Delectricity source This hospital gets electricity from PLN, which comes from Tapan Diesel Power Plant (PLTD). PLTD is a power plant that still uses fossil energy, so it is one of the strong reasons refor conducting an energy audit at Pratama Tapan Hospital. In addition, it was based on interviews ¹⁰ with staff that this hospital has never undertaken an electrical energy audit. Therefore, an electrical \mathbf{T} energy audit in this hospital is the right thing to do.

The main objective of this research is to conduct an electrical energy audit of all rooms in the Primary Hospital to obtain the amount of electrical energy used, determine the Electricity Consumption Intensity (ECI), analyze opportunities for electrical energy savings, and make recommendations for replacing electrical equipment or upgrading technology that can be done at the Primary Hospital of Tapan. However, this upgraded technology will focus on lighting classification. As for air conditioning, it is difficult to do for several reasons, namely, the uneven installation of air conditioners in all inpatient rooms, and according to interviews conducted, the lack of air conditioning use may be due to social, cultural, or climate in the local area.

2 Methodology

Place and Time of Research 2.1

This research was conducted at Pratama Tapan Hospital. This hospital is located at Tapan-Padang Street, Basa Ampek Balai Tapan District, Pesisir Selatan Regency, West Sumatra Province. This Sheet, basa Amper Data Tupan Dienter, Tabar a ward, mortuary, operating room, maternity clinic, alaboratory, emergency room, and waiting room. The time used for data collection in this research 0 was in April 2023 and used data from the previous year.

lam 2.2 **Research Design**

S

y of

Sultan Syarif Kasim

R

ic The authors conducted an energy audit research design through two stages in this research. First, cplanning an initial audit to determine the current energy usage at the Pratama Tapan Hospital using the energy or electricity payment account method and second, preparing a detailed follow-up energy audit to obtain the results of whether the current energy use is included in the energy-efficient category adjusted to the ECI standard. The flowchart explains the stages of the research carried out can be seen in Figure 1.



b a


Itan

Syarif Kasim

R

Hak Cipta Dilindungi Undang-Undang

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber



2.3 Data Collection Technique

In this research, the authors conducted two primary data collection techniques. The first is to make observations; observations in this research were carried out by looking at the lighting system, cooling, and the use of electrical energy in all work units or rooms in the Pratama Tapan Hospital. This observation aims to find out how the use of electrical energy works. The second primary data collection technique is interviews with the Engineering Manager and the Finance Department. This is done to determine when electrical energy is used with high and low needs and get results such as Energy Usage data, Electricity Bill Data, Room Data, and Measurement Data at Pratama Tapan Hospital. Secondary data such as building ECI standards, ECI air-conditioned rooms, and standardization of lighting strength in this research are taken from the standardization set by the government.

2.4 Data Analysis Technique

The data analysis technique in this research is based on the Energy Consumption Index (ECI). Electricity Energy Consumption Intensity (ECI) is an indicator that represents the energy used in a building or building in a certain period. This ECI standard has been applied in various ASEAN member countries and APEC member countries. [15]. After collecting data on all electrical energy components, it will be audited with the ECI standard. The ECI standard is to see how much energy conservation has been done by the Pratama Tapan Hospital Building. The unit used to represent ECI value is kWh/m²/year. Or it can be formulated as equation (1) [5].

$$ECI = \frac{Energy Consumption (kWh)}{Building Area (m2)}$$
(1)



0

I

0

ta В

> ~ C

Q

R Q

te

C

ultan

yarif Kasim

R

Hak Cipta Dilindungi Undang-Undang

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber

σ Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.

2. Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau

e According to a study conducted by ASEAN-USAID in 1992, the standard of ECI value in Tbuildings can be seen in Table 1. 0

No	Building Type	ECI (kWh/m²/year)
1	Office	240
2	Shopping Center	330
3	Hotel and Apartments	300
4	Hospital	380

Table 1. Standard of ECI Value in Buildings

Z Based on the Regulation of the Minister of Energy and Human Resources number 13 of 2012, Othe calculation value of the intensity of electrical energy consumption in a building can be divided into two parts: buildings using air conditioning and those without air conditioning. This can be seen ^oin Table 2. N

	Criteria	ECI (kWh/m²/year)		
		With AC	Without AC	
	Highly Efficient	<8.5	<3.4	
	Efficient	8.5 - 14	3.4 - 5.6	
	Moderately Efficient	14 – 18.5	5.6 - 7.4	

If the ECI value is lower than the lower limit, the building is said to be energy efficient. Hence, it needs to be maintained by carrying out activities and maintenance in accordance with the standard procedures set by the company. If the ECI value is between the lower limit and the reference, the building is said to be somewhat efficient, so it is necessary to improve performance by tuning up. If it is between the reference and the upper limit, then the building is somewhat wasteful, so it is necessary to make some changes.

>18.5

These changes were obtained by analyzing energy-saving opportunities. Based on the results of the Energy Management Opportunity [16], several recommendations can be made to get electrical menergy savings, namely:

Recommendations that are advisory in nature so that they do not use cost investment and do not ລີ 1. change existing equipment. An example is turning off electrical equipment, such as lights and air conditioning, when unused. Islamic

Low-Cost Investment, this recommendation slightly changes the existing equipment as an example of installing a timer on the lighting automatically or installing a temperature sensor on the air conditioner so that it can regulate the existing temperature.

High-cost investment is to make changes and improvements to the existing system. Usually, these recommendations include installing power factor correction equipment and variable speed drives.

Jniversi **Light Intensity**

Wasteful

y Light intensity is the amount of light needed to illuminate a room. Light intensity must meet the Indonesian National Standard (SNI). The light intensity is measured using a Luxmeter. Calculating othe light intensity in the room can be found using equation (2).

$E = \frac{N \times \Phi \times L}{2}$	<u>LLF×Cu×n</u>	(2)
L –	А	(2)

where, S

Ε : Light intensity (Lux)

: Number of light points Ν

>7.4



Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber

0
T
đ
a
=
3
Q
Ξ
2
≝.
E C
a
a
2
ų.
C
3
0
ar
õ

()
0
-
a 3
3
7
_
₹3.1
X
-
Zbui
Z
S
-

S X 2 R Q

0

Т

B

x

Φ	: Lumen Value
LLF :	Light Loss Factor (0.8)
Cu	: Coefficient of Utilization (0.7)

Results and Discussion

Results

: Number of lights in one point n

А : Number of lights in one point (m^2)

1

Data on building/space area is obtained from the data collection. The Pratama Tapan Hospital building has a total area is 15.120,70 m2. The detailed information can be seen in Table 3.

Load	Room Name	Area (m ²)
105 kVa	Treatment Room	9,670.5
	Mortuary Room	180
	Operation Room	150
	Maternity Clinic	1,440
	Laboratory	430.2
	Emergency Room	2,450
	Waiting Room	800
Fotal Area		15,120.70

Table 3. Data of Building Area

The use of electrical energy in Tapan Primary Hospital is divided according to the classification of lighting, cooling/air conditioning, and health or other electronic equipment that requires electrical energy, which can be seen in Table 4 (see: https://shorturl.at/hDK28).

Table 4 shows the results of checking electrical equipment in each room at Pratama Tapan Hospital. The type of lamp used already uses LED lights. The use of electrical equipment in each room varies based on needs. The air conditioner used is 2pk with 1,920 watts, 1.5pk with 1,170 watts, and 0.5pk with 340 watts.

able 5. Power	Usage by	Classification
---------------	----------	----------------

Classification	Power (Watt)	
Lighting	5,469	
Cooling/AC	37,730	
Electronics	47,859	

Islamic In Table 5, the highest power usage is in the electronics classification, while the most minor electrical energy usage is in the lighting classification.

C For the percentage of use can be seen in Figure 2, where 53% of the electronic classification NIN V supplies the most electrical energy users. While lig electrical energy users in Pratama Tapan Hospital. supplies the most electrical energy users. While lighting is only about 6% of the overall supply of

USKAR

R

State



σ



0

I

B × 0 0



- a

- Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.

2. Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau



C

S

yarif Kasim

R





Fig. 2. Percentage of Electric Energy Usage

The source of electrical energy for Pratama Tapan Hospital is supplied from PLN, with a power \circ of 105,000 VA. At the same time, the total building area is 15,120.70 m² with a power tariff group (S-2 / L). Furthermore, kWh data used to conduct this energy audit is data on the use of installed or used electrical loads. Figure 3 shows energy consumption (kWh) per month in a year.



From Figure 3, the use of electrical energy varies during the year. The lowest use of electrical energy in March amounted to 11,851 kWh, and the most extensive use in August amounted to 13,868 $\mathbf{x}^{\text{chergy in Nutren another to transform of the duration of use of electronic devices in the hospital.$

Initial Energy Audit

a Judging from the average electrical energy used in Pratama Tapan Hospital, the ECI value can be calculated. It is known that the total value of electrical energy consumption a year is 156,210.7 kWh, and the building area is 15,120.7 m². So that the ECI value is obtained from equation (1) by

$$\text{ECI} = \frac{156,210.7}{15,120.7} = 10.33 \text{ kWh} \text{ m}^2 \text{ year}$$

Jnive rs The resulting ECI value is 10.33 kWh/m²/year. Based on the standard ECI value from ASEAN-USAID, the use of electrical energy at the Pratama Tapan Hospital can be very efficient because it is very small compared to the standard value of 380.

Figure 4 presents the ECI value per month in January-December 2022. The lowest ECI value is in March, and the highest is in August. When viewed from the room-specific ECI value based on E air-conditioned and non-air-conditioned rooms from Table 2, it can be said that the monthly ECI svalue is very efficient. Several possibilities can cause ECI values that are very small from this 🔁 standard.



b a

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber

Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.

0

I

B

×

0

0


a

В

×

z

S



Based on the results of interviews from the Pratama Tapan Hospital stated that first, low energy usage is due to room facilities that do not meet the standards, as seen in the ten inpatient rooms; 4 of them only use fans as air conditioners. Second is the low number of patients and inpatients, so the use of electrical energy is low. Third, low electrical energy usage can be caused because room facilities that have met the standards have yet to be used optimally. The use of health electronics in this hospital is not very significant. This is because the patients are not too crowded.

3.3 Detailed Energy Audit

1. ECI Value of Air-Conditioned Room

A detailed energy audit is carried out by calculating the ECI of air-conditioned rooms at Pratama Tapan Hospital based on the results of calculations with the effective energy use of electricity for one month or 26 working days, apart from the emergency room, which is full for one month. This measurement uses effective working time, which is 8 hours per day. Table 6 shows the ECI measurement value and criteria for each air-conditioned room in Pratama Tapan Hospital based on the standardization of the Minister of Energy and Mineral Resources Regulation No. 13 of 2012.

No Room Name		Area (m ²)	kWh / month	ECI / month	Criteria
1	Emergency Room	53.8	943.9	17.6	Moderately Efficient
2	ICU	16.0	184.9	11.6	Efficient
3	Perinatology	18.8	288.3	15.3	Moderately Efficient
4	Resuscitation	32.0	354.4	11.1	Efficient
5	Director	38.6	409.3	10.6	Efficient
6	Accreditation	24.4	253.3	10.4	Efficient
7	Head of Subdivision	22.3	409.9	18.4	Moderately Efficient
8	Head of Finance	34.4	324.5	9.4	Efficient
9	Head of Service	25.8	411.8	16.0	Moderately Efficient
10	Head of Support	28.4	467.7	16.9	Moderately Efficient
11	Mosque	48.0	419.3	8.7	Efficient
12	The Hall	96.0	755.0	7.9	Highly Efficient
13	Archive	16.0	184.7	11.5	Efficient
14	Assets	16.0	184.7	11.5	Efficient
15	Operation	28.0	494.2	17.7	Moderately Efficient
16	CCSD	6.0	95.1	15.8	Moderately Efficient
17	VK	67.5	783.1	11.6	Efficient
18	Obstetrics Clinic	24.0	176.2	7.3	Highly Efficient

Table 6. ECI Value of Air-Conditioned Room



Б a

0

I

B × 0 0 ta

milik

S Sn

	Hak
5	Cipta I
	Dilindungi
•	Undang-Undang

1. Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber

State **Islamic University of Sultan Syarif Kasim** R

No	Room Name	Area (m ²)	kWh / month	ECI / month	Criteria	
19	Hospitalization	54.0	419.3	7.8	Highly Efficient	
20	Radiology	27.8	487.3	17.5	Moderately Efficient	
21	TCM	20.0	253.3	12.7	Efficient	
22	Pharmacies	32.0	253.3	7.9	Highly Efficient	
23	Internal Medicine Clinic	17.5	253.3	14.5	Moderately Efficient	
24	Dental Clinic	16.6	306.7	18.5	Moderately Efficient	
25	Surgery	16.6	253.3	15.3	Moderately Efficient	
26	Medical Rehab	14.0	179.7	12.8	Efficient	
27	Pediatric Clinic	16.6	253.4	15.3	Moderately Efficient	
28	General Poly	14.0	179.7	12.8	Efficient	
29	Supervisor's Room	8.6	75.3	8.7	Efficient	

X From Table 6, the ECI value for air-conditioned rooms in Pratama Tapan Hospital based on Q effective assumptions of electrical energy has varying criteria. However, the ECI value is still within The scope of efficiency. Therefore, this needs to be maintained by the Hospital so that Electric Energy ²⁰ savings can continue to be implemented.

2. Lighting Load Calculation

Measurement of lighting intensity at Pratama Tapan Hospital using a lux meter. Sampling lighting intensity data made measurements at each point in the workspace. Table 7 shows the results of the survey of lighting intensity measurements in each room along with comfort standards for workspaces based on the Directorate of Medical Support Services and Health Facilities of the Directorate General of Health Efforts of the Ministry of Health of the Republic of Indonesia in 2014 for Type D Hospitals.

NT.	Room Name	Lighting	Temperature	
No		Measurement	SNI	(°C)
1	Inpatient Room 1	50	200	30.5
2	Inpatient Room 2	47	200	30.2
3	Inpatient Room 3	48	200	31.1
4	Inpatient Room 4	48	200	30.4
5	Inpatient Room 5	49	200	30.4
6	Inpatient Room 6	50	200	31.2
7	Inpatient Room 7	55	200	31.2
8	Inpatient Room 8	52	200	31.8
9	Inpatient Room 9	50	200	31.5
10	Inpatient Room 10	52	200	31.4
11	Adult Guard Room	192	200	30.7
12	Child Guard Room	68	100	30.6
13	Radiology	67	200	30.2
14	Radiology Guard Room	65	100	30.2
15	Medical Records	50	100	30.4
16	Pediatric Clinic	58	250	30.6
17	Dental Clinic	57	250	30.6
18	Internal Medicine Clinic	56	250	30.6
19	General Poly	54	250	31.7
20	Surgery	56	250	30.6
21	Guard the Cashier	59	100	30.2

Table 7.	Results of	Light Intensit	y Measurement



0

Т

B

×

0

5

ta

milik

S Sn

×

Q

R

B

State Islamic

yarif Kasim

R

Hak Cipta Dilindungi Undang-Undang

Р Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber

- 2. Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau
 - a
 - Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.

Lighting In Temperature No **Room Name** Measurement SNI (°C) 22 500 31.7 Operation 51 23 **Operation Guard Room** 47 100 31.6 24 **Obstetrics** Clinic 50 200 31.6 25 48 100 27.5 Public Restroom 26 57 100 Panel 31.7 27 58 100 31.4 Laundry 28 Nutrition Room 53 100 31.3 29 Gas chamber 55 200 31.3 30 Nutrition Break Room 58 100 31.2 250 31.2 31 EMERGENCY ROOM 55 32 Pharmacies 52 200 31.0 33 53 100 31.2 **Emergency Room** 34 200 Medicine Warehouse 47 31.6 35 ICU 43 200 31.6 36 200 Director's Room 58 31.5 37 Archive Room 64 100 31.6 38 Head of Sub-Division 58 200 31.6 Room 39 Head of Service 50 200 31.6 40 58 200 31.6 Head of Support 41 57 200 31.6 Mosque 42 100 The Hall 46 31.6 43 Supervisor 58 200 31.3 44 Perinatology 54 500 30.5 45 85 500 30.2 Resuscitation 63 200 31.2 46 Accreditation 47 Head of Finance 54 200 30.8 77 48 100 30.6 Asset Room 49 Mortuary Room 68 100 30.5 50 200 31.4 Dressing Room 65 200 31.5 51 CCSD 54 52 VK 86 500 30.8 53 VK Guard Room 48 100 31.6 54 200 TCM 59 30.5 58 500 55 Labor 30.8 Medical Rehab 50 200 30.4 56

C Based on the results of the lighting intensity measurements in Table 7, it is still not up to standard. Based on the results of the lighting intensity measurements in Table 7, it is still not up to standard. This condition can be more efficient regarding energy use, but working comfort will be reduced. Because the results of the overall energy consumption of the building are still very efficient, adding amp points to increase room lighting is still very possible, or replacing larger lamp power to meet Lux standards for the room.

P3. **Lighting Change Recommendations**

For light intensity data that has yet to meet the predetermined standards, it is necessary to change S E the number of lamp points and power used. The type of lamp used in each room is LED. The selection of lamps for lighting in this hospital is already said to be efficient. Given that LEDs are alamps with small energy consumption and long service life. But to improve the lighting of LED columps used must be a larger wattage and an increase in the number of lamps so that the desired



Hak Cipta Dilindungi Undang-Undang

0

Т

Lighting standards are by Minister of Health Regulation No. 24 of 2016 standards. Table 8 shows the recommended lamp replacement and the lux value resulting from the lamp replacement. Table 8. Results of Lighting Replacement Recommendations

a m	No Room Name		Substitution Recommendation LED Light			Lux		
Ξ			13W	19W	55W	LT*	SNI	LR*
F	1	Inpatient Room 1		12		50	200	212.8
6	2	Inpatient Room 2		12		47	200	212.8
5	3	Inpatient Room 3		12		48	200	212.8
Z	4	Inpatient Room 4		12		48	200	212.8
S	5	Inpatient Room 5		12		49	200	212.8
	6	Inpatient Room 6		12		50	200	212.8
SK	7	Inpatient Room 7		12		55	200	212.8
a	8	Inpatient Room 8		12		52	200	212.8
π	9	Inpatient Room 9		12		50	200	212.8
la	10	Inpatient Room 10		12		52	200	212.8
n	11	Adult Guard Room	2			192	200	218.4
	12	Child Guard Room	2			68	100	107.0
	13	Radiology		6		67	200	206.4
	14	Radiology Guard Room		1		65	100	132.6
	15	Medical Records		10		50	100	141.1
	16	Pediatric Clinic		5		58	250	289.1
	17	Dental Clinic		5	12 S. H.	57	250	289.1
	18	Internal Medicine Clinic		6		56	250	328.7
	19	General Poly		4	R. 1998	54	250	273.6
	20	Surgery		5		56	250	289.1
_	21	Guard the Cashier	4		2.54	59	100	210.0
	22	Operation			6	51	500	594.0
_	23	Operation Guard Room	1			47	100	109.2
	24	Obstetrics Clinic	8			50	200	218.4
St	25	Public Restroom	2			48	100	187.2
tate	26	Panel		3		57	100	119.7
e	27	Laundry	2			58	100	145.6
S	28	Nutrition Room		6		53	100	112.0
lam	29	Gas Chamber		4		55	200	240.0
3	30	Nutrition Break Room	2			58	100	172.4
0	31	Emergency Room		_	5	55	250	257.8
C	32	Pharmacies		7		52	200	209.5
niv	33	Emergency Room		1		53	100	124.7
Ve	34	Medicine Warehouse	2	3		47	200	252.0
ersity	35	ICU Director la Presenta	2	TTT	2	43	200	81.90 215.2
it	36 37	Director's Room Archive Room	3		3	58 64	200	122.9
1.2	37		3		JANA		100	
of	38	Head of Sub-Division Room		5		58	200	215.1
S	39	Head of Service		6		50	200	222.7
E	40	Head of Support		6		58	200	202.5
ultan	41	Mosque		11		57	200	202.5
	40	The Hall		11		46	100	109.7
Syarif Kasim Ri	43	Supervisor		2		58	200	221.7
a						00	200	
E								
7								
a								
Sil								
B								
R								

- 1. Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber: a. Pengutipan hanya untuk kepentingan pendidikan, penelitian, penulisan karya ilmiah, penyusunan laporan, penulisan kritik atau tinjauan suatu masalah.
- b. Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau.
- 2. Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau



0

T

	No	Room Name	Substitution Recommendation LED Light			Lux		
2			13W	19W	55W	LT*	SNI	LR*
5	44	Perinatology			4	54	500	588.5
<u>ہ</u>	45	Resuscitation			6	85	500	519.7
7 4	46	Accreditation			2	63	200	227.6
-	47	Head of Finance		8		54	200	222.7
-	48	Asset Room	3			77	100	122.9
	49	Mortuary Room	2			68	100	124.8
	50	Dressing Room	2			65	200	218.4
Z	51	CCSD	3			54	200	327.6
S	52	VK			13	86	500	533.9
	53	VK Guard Room	1			48	100	109.2
S	54	TCM		5		59	200	239.4
â	55	Labor		- A -	4	58	500	525.0
_	56	Medical Rehab		3		50	200	205.2
* LT: Measured Lux								

Sector Secto

⊆

Isla

B

Syarif Kasim

R

1 - 7,

After obtaining the results in the form of recommendations by changing the number of light points (N) and lamp power in the lighting system at Pratama Tapan Hospital, the results of the calculation of lighting strength in each room are obtained using equation (2).

The calculation of lux value after lamp replacement is shown in Table 8, namely: Inpatient Room

$$E (LR) = \frac{N \times \Phi \times LLF \times C_{\underline{u}} \times n}{A}$$

= $\frac{12 \times 1.710 \times 0.8 \times 0.7 \times 1}{54}$
= $\frac{11.491,2}{54}$ = 212,8 Lux

After calculating the recommended lux value (LR) using recommendation data in the form of changing the number of lamp points (N) and lamp power, the results obtained in the form of an increase in lighting strength (Lux) are appropriate and have met the lighting standards of SNI 03-6197-2000 [16].

Conclusion

Based on the calculation of the use of electrical energy in the Pratama Tapan Hospital, amounting to 38,296 watts with the most significant energy use found in the cooling/air conditioning load of 53% and the lowest is the lighting load of 5% of the total calculated power. While the results of the use of electrical energy in the Primary Hospital based on the Energy Consumption Intensity (ECI) standard after the measurement is very efficient, which amounted to 10.33 kWh/m²/year. Therefore, the hospital must maintain this condition so that the ECI value is always in a highly efficient position. The small value of Energy Consumption Intensity (ECI) is due to several factors, one of which is that the room facilities at the Pratama Tapan Hospital do not meet the standards.

The lighting system in the Pratama Tapan Hospital room still does not meet the Lux SNI standard Stated in the SNI 03-6197-2000 standard, so it is necessary to change the number of lamp points (N) and power on the lamp so that the lighting strength in each room meets the minimum lighting.



Б

0

Т

ax5

C

0

Q

₹.6

∼[1]

U N

S

Sn

⊼[2] Q

R

a^[3]

Islamic University of

Sultan Syarif Kasim

R

Acknowledgment

Thank you to the director of the Pratama Tapan Hospital, who has made it easy to obtain the data needed in this research. As well as to hospital employees who assisted in collecting data.

References

D. J. E. B. T. dan K. E. (EBTKE)., "Hebat, Indonesia Salah Satu Negara Dengan Tingkat Efisiensi Energi Tertinggi!,", 2017. [Online], Available on: https://ebtke.esdm.go.id/post/2017/03/16/1593/indonesia.peringkat.23.konsumsi.energi.tert 2017 %7C inggi.dunia#:~:text=Kamis%2C 16 Maret 15%3A00 WIB %7C,%28AS%29%2C American Council for An Energy-Efficient Economy %28ACEEE%29 (accessed May 08, 2023).

A. Martin, "Audit Energi Sistem Tata Cahaya dan Tata Udara pada Basement dan Lantai 1 Toko Buku Pekanbaru," JTM-ITI (Jurnal Tek. Mesin ITI), vol. 6, no. 2, 2022, [Online], Available on: https://jtmiti.org/index.php/JTM/article/view/762/pdf.

M. Dongellini, C. Marinosci, and G. L. Morini, "Energy audit of an industrial site: A case study," Energy Procedia, vol. 45, pp. 424–433, 2014, [Online], Available on:

https://www.semanticscholar.org/paper/Energy-Audit-of-an-Industrial-Site%3A-A-Case-Study-Dongellini-Marinosci/a9f43614440a6c45d6013b4e43d9d27bf3414e4a.

[4] H. Mahmood, D. Michaelson, and J. Jiang, "Accurate reactive power sharing in an islanded microgrid using adaptive virtual impedances," IEEE Trans. Power Electron., vol. 30, no. 3, 2015. doi: 10.1109/TPEL.2014.2314721, [Online], Available on: https://ieeexplore.ieee.org/abstract/document/6781578.

- [5] A. A. Rahmawati and S. Abduh, "Audit Energi Gedung Kampus A Universitas Muhammadiyah Tangerang untuk Penerapan Sistem Manajemen Energi Berbasis ISO 50001: 2018," vol. 14, no. 2, pp. 187-195, 2023, doi: 10.33322/energi.v14i2.1715, [Online], Available on: https://jurnal.itpln.ac.id/energi/article/view/1715.
- D. Despa, G. F. Nama, T. Septiana, and M. B. Saputra, "Audit Energi Listrik Berbasis Hasil [6] Pengukuran dan Monitoring Besaran Listrik pada Gedung A Fakultas Teknik Unila," Electrician, vol. 15, no. 1, 2021, doi: 10.23960/elc.v15n1.2180, [Online], Available on: http://repository.lppm.unila.ac.id/31418/1/2180-Article%20Text-582-1-10-State 20210209%20%282%29.pdf.

Y. N. Choir and D. Irawan, "Audit Energi Listrik Gedung Baru Universitas Muhammadiyah Gresik," Power Elektron. J. Orang Elektro, vol. 12, no. 1, p. 8, 2023, doi: 10.30591/polektro.v12i1.4699, [Online], Available on: https://ejournal.poltektegal.ac.id/index.php/powerelektro/article/view/4699.

S. Oktavia Ginting, I. B. G. Manuaba, and A. A. G. Maharta Pemayun, "Audit Energi untuk Pencapaian Penghematan Penggunaan Energi Listrik di PT. Graha Sarana Duta II Denpasar," J. Spektrum, vol. 9, no. 1, 2022, doi: 10.24843/spektrum.2022.v09.i01.p4,

[Online], Available on: https://www.academia.edu/105877052/Audit Energi Untuk Pencapaian Penghematan P $enggunaan_Energi_Listrik_DI_Pt_Graha_Sarana_Duta_II_Denpasar.$

A. Kumar, S. Ranjan, M. B. K. Singh, P. Kumari, and L. Ramesh, "Electrical Energy Audit in Residential House," Procedia Technol., vol. 21, pp. 625-630, 2015, doi: 10.1016/j.protcy.2015.10.074, [Online], Available on: https://www.sciencedirect.com/science/article/pii/S2212017315003023.

A. Sendrayaperumal et al., "Energy Auditing for Efficient Planning and Implementation in Commercial and Residential Buildings," Adv. Civ. Eng., vol. 2021, 2021, doi: 10.1155/2021/1908568. [Online], Available on: https://www.hindawi.com/journals/ace/2021/1908568/.

. Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber

Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau

Hak Cipta Dilindungi Undang-Undang

2. Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau



0

I

×

C

2

З

Sn

a[15]

a [16]

R

[11] ه

0[12]

—[13]

I. N. Darmawan, "Simulasi Audit Energi pada Rumah Sakit Umum Daerah Banyumas," J-Proteksion, vol. 5, no. 2, 2021, doi: 10.32528/jp.v5i2.4130, [Online], Available on: http://jurnal.unmuhjember.ac.id/index.php/J-Proteksion/article/view/4130.

H. Eteruddin, A. Rahman, M. P. Halilintar, and A. Tanjung, "Evaluasi Indeks Konsumsi Energi Listrik Di Rumah Sakit Islam Ibnu Sina Pekanbaru," J. Elektro dan Mesin Terap., no. Vol. 7 No. 2 (2021), 2021, doi: 10.35143/elementer.v7i2.5173, [Online], Available on: https://jurnal.pcr.ac.id/index.php/elementer/article/view/5173.

M. Saputra and A. Hamzah, "Studi Analisis Potensi Penghematan Konsumsi Energi melalui Audit dan Konservasi Energi Listrik di Rumah Sakit Universitas Riau," J. Online Mhs. Fak. Tek. Univ. Riau, vol. 4, no. 1, pp. 1-13, 2017, [Online], Available on: https://jom.unri.ac.id/index.php/JOMFTEKNIK/article/view/14677.

S. Alhurayess and M. K. Darwish, "Analysis of energy management in hospitals," 2012, 10.1109/UPEC.2012.6398665, doi: [Online], Available on: https://ieeexplore.ieee.org/abstract/document/6398665.

S. Suhendar, "Audit Sistem Pencahayaan dan Sistem Pendingin Ruangan di Gedung Rumah Sakit Umum Daerah (RSUD) Cilegon," Setrum Sist. Kendali-Tenaga-elektronikatelekomunikasi-komputer, vol. 2, no. 2, 2016, doi: 10.36055/setrum.v2i2.486, [Online], Available on: https://jurnal.untirta.ac.id/index.php/jis/article/view/486.

B. S. N. (BSN), "SNI 03-6197-2000 Konservasi Energi Pada Sistem Pencahayaan," 2000, [Online], Available on.

https://www.academia.edu/38603934/SNI_03_6197_2000_Standar_Nasional_Indonesia_ Badan_Standardisasi_Nasional_Konservasi_energi_pada_sistem_pencahayaan.

7 Authors

Nanda Okta Putra is a student who is currently studying in the Bachelor of Electrical Engineering study program, Faculty of Science and Technology, Sultan Syarif Kasim Riau State Islamic University. (Email: nandaoktaputraa@gmail.com)

Zulfatri Aini is a lecturer majoring in electrical engineering in Energy concentration. She completed her education with a Bachelor of Engineering Science at STTP University of Padang. She continued her education with a Master of Engineering at Gajah Mada University Yogyakarta and Pearned a Doctoral degree at Padang State University.

Dila Marta Putri is a lecturer majoring in electrical engineering at the Riau Institute of Business Technology. She completed her education with a Bachelor of Engineering at State Islamic University of Sultan Syarif Kasim Riau. She continued her education with a Master of Engineering at the Sepuluh Nopember Institute of Technology in Surabaya.

UIN SUSKA RIAU

R

2. Dilarang mengumumkan dan memperbanyak sebagian atau seluruh karya tulis ini dalam bentuk apapun tanpa izin UIN Suska Riau Pengutipan tidak merugikan kepentingan yang wajar UIN Suska Riau

Dilarang mengutip sebagian atau seluruh karya tulis ini tanpa mencantumkan dan menyebutkan sumber